



G 25 Mobile Generator, Skid Mounted

Item Number: 0620344

G 25

Heavy-duty mobile generator for reliable power

>> Compact, sound-attenuated generator provides single and three-phase power for construction, commercial, industrial and special event applications where quiet, reliable power is needed. A solid state digital information center monitors generator output and engine functions plus provides protection against engine and generator faults as well as standard automatic remote starting for standby applications. Skid-mounted units feature a fully integrated, large capacity fuel tank for long run times, even without a trailer. <<



Additional Advantages

- Unit offers low noise, mobile power for virtually any sound-sensitive application. Utilizing proven technology and simple design, this quiet generator provides excellent reliability in the most demanding environments.
- Brushless generator features a separate excitation winding for excellent motor starting and an enhanced ability to run non-linear loads.
- Durable features like stainless steel external hardware and automotive corrosion treatment of select body parts provide a long-lasting, quality appearance ensuring a high resale value.
- Generator control panel swings open as one complete unit for easy servicability.
- Factory-installed customized options are available. These include, but are not limited to, a fluid containment system, cold weather options, camlock panel, etc.
- Optional single-axle trailers are fully equipped and highway ready with DOT lighting, chains, height adjustable coupler and electric or hydraulic surge brakes.

Description	Metric	Imperial
Length x width x height (skid mounted)	1946 x 889 x 1130 mm	76.6 x 35 x 44.5 in
Operating weight, Skid mounted	1057 kg	2332 lb
Dry weight, Skid mounted	867 kg	1911 lb
Generator with optional trailer Length x width x height	3378 x 1524 x 1753 mm	133 x 60 x 69 in
Operating weight with optional trailer	1271 kg	2802 lb
Dry weight with optional trailer	1080 kg	2381 lb
Standby output	20.4 / 25.5 kW/kVA	20.4 / 25.5 kW/kVA
Prime output	19.5 / 24.4 kW/kVA	19.5 / 24.4 kW/kVA
AC voltage 1 Ø	120, 127, 139, 240, 254, 277 V	120, 127, 139, 240, 254, 277 V
AC voltage 3 Ø	208, 220, 240, 416, 440, 480 V	208, 220, 240, 416, 440, 480 V
Frequency	60 Hz	60 Hz
Power factor (1 phs / 3 phs)	1.0 / 0.8	1.0 / 0.8
Sound level	65 dB(A)	65 dB(A)
AC receptacles 1 Ø120V - 20 amp GFI duplex	2	2
AC receptacles 1 Ø120/240V - 50 amp twist lock	1	1
AC receptacles 1 Ø120/240V - 30 amp twist lock	1	1
Engine Type	Isuzu 2.2 L	
Displacement	2179 cm ³	133 in ³
Max. Rated Power at Rated Speed*	26.4 kW at 1800 rpm	35.4 hp at 1800 rpm
Power Rating Specification	SAE J1995, ISO 8528-1	SAE J1995, ISO 8528-1
Battery	12V/750CCA	12V/750CCA
Voltage regulation no load to full load	+/-1%	+/-1%
Voltage regulation steady state	+/-0.2%	+/-0.2%
Insulation class	H	H
Generator type	Brushless w/ AVR	Brushless w/ AVR
Fuel consumption (full load) with / without generator	6.8 l/h	1.8 US gal/h
Fuel tank capacity	221 l	58.4 US gal
Run time	100% - 32.2 h	100% - 32.2 h
Trailer hitch type	2" Ball	2" Ball

Standard Package - G 25

Above package includes operator's manual and parts manual. Generator trailers and generator units sold separately.

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

15749 Lyons Valley Rd.
Jamul, CA 91935
800-341-7027
HardyDiesel.com

